

FIXED BOLLARD: 114/900 Semi-Domed Top

Operation Types: Fixed & With Machine Bands



ATG ACCESS



PRODUCT OVERVIEW

The 114/900 Fixed bollard provides commercial and industrial perimeters with a strong and elegant solution for demarcation, a visual deterrent to ram-raid attacks and to prevent vehicles mounting kerbs or paths where pedestrians could be.

The height of the bollard coupled with two, yellow reflective bands creates increased visibility for larger vehicles such as vans or even HGV's, clearly marking a restricted zone or area for drivers.

The construction of the product consists of a strong, steel tube measuring 114 mm in diameter and 1,300 in length. The bollard is either supplied galvanised for high level corrosion protection or shot blasted and then powder coated to a standard RAL colour.

The wall thickness when supplied in either option is 5 mm. The product can also be supplied if preferred in stainless steel Grade 304. The wall thickness in this instance would be 6 mm.

This type of construction has a major advantage in that the dense wall thickness makes the product a lot stronger than many bollards which just have a 2-3 mm wall and are very susceptible to denting and bending.

The product is root fixed and installation is very straightforward.

If the product is being installed within a particularly saline or marine environment, we would recommend using Grade 316 stainless steel. Price on application.

APPLICATIONS

Suitable for demarcation, a high visibility deterrent against ram-raid attacks and to prevent vehicles from mounting kerbs or paths.

FINISHES

Supplied in a variety of finishes; hot dip galvanised, shot blasted and then powder coated to any standard RAL colour or supplied in a Grade 304 stainless steel finish. All variants have a semi-domed top & two machine bands as standard measuring 25 mm in depth.

114 900 FIXED SECURITY BOLLARD STATISTICS

114/900 Fixed Bollard	
Bollard Diameter	114 mm
Height Above Ground	900 mm; product supplied in an overall length of 1,300 mm
Foundation Depth	400 mm (approx.).
Finishes Available	Bollard is supplied either galvanised, shot blasted and then powder coated to any standard RAL colour or in Grade 304 stainless steel. Finished with a semi-domed top & two yellow, reflective bands. The bands are fitted within machined recesses measuring 25 mm in depth. Grade 316 stainless steel is possible, price on application.
Wall Thickness	Galvanised or Powder Coated Variants – 5 mm; Stainless Steel Variant – 6 mm.