

FIXED BOLLARD: 114/900 Semi-Domed Top

Operation Types: Fixed & without reflective bands



ATG ACCESS



PRODUCT OVERVIEW

The 114/900 Fixed bollard provides commercial and industrial perimeters with a strong and elegant solution for demarcation, a visual deterrent to ram-raid attacks and to prevent vehicles mounting kerbs or paths where pedestrians could be.

The height of the bollard allows increased visibility for larger vehicles such as vans or even HGV's, clearly marking a restricted zone or area for drivers.

The construction of the product consists of a strong, steel bollard measuring 114 mm in diameter and 1,300 in length. The bollard is available in a variety of finishes; mild-steel and then galvanised for high level corrosion protection, or shot blasted

and then powder coated to a standard RAL colour, both with a wall thickness of 5 mm. Alternatively, the product can be supplied in Grade 304 stainless steel with a wall thickness of 6 mm.

This type of construction has a major advantage in that the bollard wall thickness makes this product a lot stronger than many bollards which have a wall measuring 2-3 mm thick and are very susceptible to denting and bending.

The product is root fixed and installation is very straightforward. If the product is being installed within a particularly saline or marine environment, we would recommend using Grade 316 stainless steel.

APPLICATIONS

Suitable for demarcation, a high visibility deterrent against ram-raid attacks and to prevent vehicles from mounting kerbs or paths.

FINISHES

Either in galvanised mild steel, shot blasted and then powder coated to a standard RAL colour or supplied in Grade 304 stainless steel with a semi-domed top. Grade 316 is available if required.



114 900 FIXED SECURITY BOLLARD STATISTICS

114/900 Fixed Bollard	
Bollard Diameter	114 mm
Height Above Ground	900 mm; product supplied in an overall length of 1,300 mm
Foundation Depth	400 mm (approx.).
Finishes Available	Bollard supplied in either galvanised mild steel, shot blasted and then powder coated to any standard RAL colour or in Grade 304 stainless steel. Finished with a semi-domed top. Grade 316 is available and recommended for saline environments, price on application.
Wall Thickness	Galvanised or Powder Coated – 5 mm; Stainless Steel – 6 mm.