

114 670 SECURITY BOLLARD (LIGHTWEIGHT)

Operation Types: Lift-Out (Removable)



ATG ACCESS



PRODUCT OVERVIEW

The 114/670 security bollard range (lightweight) includes a lift-out, static and fully telescopic model to suit multiple security objectives. With a wall thickness of 3.2 mm, despite the products diameter and size, the bollard is lightweight enough to be able to remove and store when not needed.

LIFT OUT BOLLARD

Removable bollards are a great security solution for sites with insufficient room to dig a full depth foundation for a retractable bollard. The required foundation depth is reduced by 50% compared with the fully retractable equivalent.

Lift-out bollards also provide a security solution for sites with a high water table. Retractable bollards are not effective within

this installation scenario and daily operation of the product, sitting in water becomes very difficult. Having a removable bollard avoids this issue whilst still providing heavy duty site security.

To operate the product, you simply turn the key in the lock, twist the handle and detach the product from the installed socket. The lid can then be closed and vehicle access is possible. To secure and restrict vehicle access again you lift up the lid, re-fit the bollard back into the socket and then push the lock down with your thumb.

Spare storage sockets can be purchased to minimize scratching and damage when the security bollard is not in use and being stored.

CERTIFICATION

Manufactured in the UK and to the quality standard, BS: ISO 9001.

FINISHES

Available in stainless steel only; this product comes with two reflective bands as standard and a black 'T-Bar' handle.

114 670 SECURITY BOLLARD STATISTICS (LIGHTWEIGHT)

	Lift-Out Bollard
Bollard Diameter	114 mm
Height Above Ground	658 mm (exc. handle)
Foundation Depth	450 mm
Finishes Available	Stainless steel only with two, yellow reflective bands and a black 'T-Bar' handle.
Lifting Weight	9.7 kg
Wall Thickness	3.2 mm

