

ATG 101/670 SQUARE BOLLARD

Operation Type: Telescopic, Lift-Out & Fixed



ATG ACCESS



CERTIFICATION

Manufactured to the BS: ISO 9001 quality standard. Tested to the Sold Secure, security standard and insurance company approved.

FINISHES

Supplied hot dip galvanised as standard with two yellow reflective bands. This range can also be nylon coated to any specified RAL colour to suit client requirements.

OPTIONAL EXTRAS

Sold Secure lock – high security lock; ornate security cap and spare locks & keys.

PRODUCT OVERVIEW

The 101/670 security bollard range includes a fully telescopic model as well as a lift-out and static variant to suit multiple security objectives. The product is suitable to protect applications such as a garage forecourt, commercial car parks or driveway protection. Product variants available as follows:

TELESCOPIC BOLLARD:

A fully retractable product; to operate you simply turn the key in the lock, twist the handle and lower gently into the outer casing.

The lid can then be closed, and vehicle access is possible. To secure and restrict vehicle access again you lift the lid, hold the handle, lift the product into the 'up' position and then rotate the handle and push the lock down with your thumb.

LIFT-OUT BOLLARD:

Lift-Out bollards are a great security solution for

sites with insufficient room to dig a full-depth foundation for a retractable bollard. The required foundation depth is reduced by 50% compared with the fully retractable equivalent. Lift-out bollards also provide a security solution for sites with a high-water table. Spare storage sockets are available as an optional extra to provide a safe place to store the bollard when not in use.

FIXED BOLLARD:

Static bollards are available to match the 101/670 security bollard range to secure complete perimeters.

Supplied with an overall length of 1,300 mm, these products can be installed to suit a clients preferred height above ground.



ATG 101/670 ROUND SECURITY BOLLARD RANGE

	Telescopic Variant	Lift-Out Variant	Fixed Variant
Bollard Diameter (mm)	101 mm	101 mm	101 mm
Height Above Ground (mm)	697 mm (Inc. handle)	697 mm (Inc. handle)	To suit client requirements.
Foundation Depth (mm)	1,050 mm	450 mm	Supplied in an overall length 1,300 mm
Finishes Available	Hot dip galvanised as standard.	Hot dip galvanised as standard.	Hot dip galvanised as standard.
Lifting Weight (kg)	16 kg	16 kg	N/A
Wall Thickness (mm)	5 mm	5 mm	5 mm
Optional Extras	Sold Secure Lock Ornate Cap	Sold Secure Lock Ornate Cap Spare Storage Sockets	N/A