

CITY OF LONDON FIXED BOLLARD

Operation Types: Fixed Security Bollard



ATG ACCESS



PRODUCT OVERVIEW

The ATG Access High Security City of London Bollard has the integral good looks and heritage appearance of the traditional City of London bollard which can be found all over London's square mile.

ATG Access have taken the traditional design and engineered an impact tested version of the heritage design. The impact tested variant is also available in a lift-out, or shallow foundation model.

The product is finished and painted with the distinctive black, red and white design seen across the square mile City of London.

Impact tested to withstand a high velocity attack, this product withstood impact from a 7,500 kg vehicle travelling at 80 kph.

Cast in Manganese steel, this material is incredibly robust, cannot be cut and is extremely hardwearing and corrosion resistant.

Requiring 600 mm of foundation depth, this product is ideal for applications where foundation depth is not an issue and where no restrictions apply. The foundation required, a concrete, rebar foundation with 1.2 m spacings to comply with the PAS 69.

If depth restrictions do apply, the City of London bollard is also available as a shallow foundation product - installed within a foundation depth of just 150 mm.

SECURITY RATING

Traditional Depth Static:

PAS 68: V/7,500(N2)80/90:22.7/25.0

FINISHES

Manganese steel, painted to the traditional City of London Bollard design – red, black and white. Other colours are available.

CITY OF LONDON FIXED BOLLARD

Fixed

Bollard Diameter	240 mm (base) 160 mm (top)
Height Above Ground	1,390 mm
Foundation Depth	600 mm
Finishes Available	Painted Manganese Steel – Red, Black & White
Security Rating	PAS 68: V/7,500(N2)80/90:22.7/25.0

