

101/670 BOLLARD RANGE

Operation Types: Fully Retractable, Lift-Out & Static



PRODUCT OVERVIEW

The 101/670 bollard range offers attractive aesthetics which makes the product suitable for applications such as garage forecourt protection or locations where aesthetics are a high priority. It is available in a fully retractable, lift-out, or static version.

The **Fully Retractable model** is available in a galvanised or RAL colour finish with a 5mm wall thickness and two yellow reflective bands as standard.

The **Lift-Out model** is available for sites where there is insufficient room for digging a foundation for the fully retractable model and vehicle access still needs to be restricted. The required foundation depth is reduced by 50% compared to the fully retractable model, making it suitable for areas where it is not possible to install a full outer casing. Spare storage sockets are also available to purchase with this model.

A **Static Model** of the 101/670 Bollard is also available. It can be used to protect infrastructure where vehicle access is totally prohibited such as glass shop fronts and ATM machines or to compliment the lift-out and fully retractable versions.

TO PROTECT

Entrances to commercial and retail premises, residential driveway entrances, garage door protection, and car show room security to name just a few.

FINISHES AND OPTIONAL EXTRAS

Galvanised or nylon coated with a specified RAL colour | Security cap | Sold Secure lock to increase site protection | Spare storage socket for lift-out version.

SECURITY RATING

Insurance company recommended by Aviva, AXA, Norwich Union & Allianz Insurance PLC. Approved by the Secure by Design Accreditation.

101/670 BOLLARD STATISTICS

	FULLY RETRACTABLE	LIFT-OUT	STATIC
BOLLARD DIAMETER	101mm	101mm	101mm
CASING DIAMETER	150mm	150mm	N/A
HEIGHT ABOVE GROUND	670mm	670mm	670mm
FOUNDATION DEPTH	1050mm	550mm	630mm
FINISHES AVAILABLE	GV, RC	GV, RC	GV, RC
WALL THICKNESS	5mm	5mm	5mm
LIFTING WEIGHT	16kg	16.5kg	N/A
SHIPPING WEIGHT	39.5kg	29kg	8.1kg

Key: GV – Galvanised, RC – RAL coated

Note: All fixed bollards are supplied with an overall length of 1300mm and require a minimum foundation depth of 400mm.

