

114/900 BOLLARD RANGE

Operation Types: Fully Retractable, Static or Lightweight Static



PRODUCT OVERVIEW

The ATG Access 114/900 telescopic security bollard is utilised where visibility is the key to the products installation. Due to the height of the product, it is brought to the attention of pedestrians and larger vehicles and is often utilised where large crowds of people may pass through an area. It is available in a fully retractable, static or a lightweight static version.

The **Fully Retractable model** comes with a unique lift-assist mechanism supplied as standard which enables the product to provide heavy duty robust security which can be utilised by all. The lift-assist mechanism reduces the product's lifting weight by up to 60%. Available with a galvanised or RAL colour finish with a 5mm wall thickness or in a stainless-steel version with a 6mm wall thickness. It comes with a black T-Bar handle as standard (see optional extras for alternative handle types).

A **Static model** of the 114/900 bollard is also available in two versions- heavy duty and lightweight. It can be used to protect infrastructure where vehicle access is totally prohibited such as glass shop fronts and ATM machines. Available in galvanised, any RAL colour or with a stainless-steel finish (either with a heavy duty 6mm wall thickness or a 3.2mm lightweight wall thickness). The 114/900 static bollard is available without banding and offers the option of domed, semi-domed, and sloping top.

TO PROTECT

Car showroom and garage forecourt security, university campus access control and sports stadium perimeter protection to name just a few. With an increased diameter this product offers an aesthetically pleasing bollard, more deterrent to unauthorised vehicle attack.

FINISHES AND OPTIONAL EXTRAS

Stainless-steel folding handle (not available when used with sold secure lock) | Sold secure lock | Stainless-steel static version is available in a heavy duty (6mm wall thickness) version or a lightweight (3.2mm wall thickness) version with two reflective band.

SECURITY RATING

Insurance company recommended by Aviva, AXA, Norwich Union & Allianz Insurance PLC. Approved by the Secure by Design Accreditation.

114/900 BOLLARD STATISTICS

	FULLY RETRACTABLE	STATIC (Heavy Duty)	STATIC (Lightweight)
BOLLARD DIAMETER	114mm	114mm	114mm
CASING DIAMETER	200mm	N/A	N/A
HEIGHT ABOVE GROUND	900mm	900mm	900mm
FOUNDATION DEPTH	1320mm	500mm	500mm
FINISHES AVAILABLE	GV, RC, SS	GV, RC, SS	SS
WALL THICKNESS	5 - 6mm	5 - 6mm	3.2mm
LIFTING WEIGHT	6 - 7kg	N/A	N/A
SHIPPING WEIGHT	75 – 77KG	16 - 17kg	11.0kg

Key: GV – Galvanised, RC – RAL colour, SS – Stainless-steel

Note: All fixed bollards are supplied with an overall length of 1300mm and require a minimum foundation depth of 400mm.

Schematic drawing for the 114/900 Bollard Range

